

CHESTERFELT EXTENDED PRODUCT GUARANTEE SELECTOR **FLAT ROOFING ROLL & POUR SYSTEMS**

Product Range	First Layer Selection and method of fixing depends on decking/structure or surface type and is the responsibility of the Contractor		Second Layer	Third Layer	Years of Cover
	Partial Bond or Nail on				
Chestermeric	Chesterplus BS737 3G	BS747 Chesterflex 5U (125)	Chestermeric 250	Chestermeric 350 Mineral AA Fire Rating	20 Years
Chestermeric	Chesterplus BS737 3G	BS747 Chesterflex 5U (125)	Chestermeric 250	Chestermeric 250 Mineral	15 Years
Chestermeric	Chesterplus BS737 3G	BS747 Chesterflex 5U (125)	Chestermeric 180	Chestermeric 350 Mineral	15 Years
Chesterflex	Chesterplus BS737 3G	BS747 Chesterflex 5U (125)	Chesterflex BS747 125 – 5U	Chesterflex BS747 350 5E/5B*	10 Years
	Chesterplus BS737 3G	BS747 Chesterflex 5U (125)	Strongbond 180 Sand	Chesterflex BS747 350 (2000) 5E/5B*	

***If plain finish is used 2 coats of Chesterfelt aluminium reflective coating will be required or suitable mineral chippings**

**** Chesterflex BS747 5U (125) to be only used onto timber tongued and grooved board**

Chesterfelt recommend that all products must be laid in accordance with BS8217 Code of Practise for Built up Felt Roofing

Please refer to Terms and Conditions of Guarantee

www.chesterfelt.co.uk
[Tel: 01246 268000](tel:01246268000)

The above is accurate at time of issue and can be subject to change without prior notice. Any deviations from the above must have the approval of Chesterfelt Ltd

DEBOTEC EXTENDED PRODUCT GUARANTEE SELECTOR
TORCH – APPLIED FLAT ROOFING PRODUCTS

Product Range	First Layer Selection and method of fixing depends on decking/structure of surface type and is the responsibility of the Contractor	Second Layer	Third Layer	Years of Cover
Debotec Laser Torch Gold SBS	Debovent Venting or Strongbond 180 Sand **	Laser Gold Underlay	Laser Gold Mineral	20 years
Debotec Laser Torch SBS	Debovent Venting or Strongbond 180 Sand **	Laser Torch Underlay	Laser Torch Mineral	15 Years
Debotec Deboflex APP	Debovent Venting or Strongbond 180 Sand **	Deboflex Underlay	Deboflex Plain* or Mineral	12 Years
Debotec Topguard SBS	Debovent Venting or Strongbond 180 Sand **	Topguard Underlay	Topguard Mineral	10 Years
Debotec /Deflector Plus APP	Debovent Venting or Strongbond 180 Sand **	Deflector Plus Underlay	Deflector Plus Plain* or Mineral	10 Years
Debotec Duo	Debovent Venting or Strongbond 180 Sand **	Laser Underlay	Duo Plain** or Mineral	15 Years

***If plain finish is used 2 coats of Chesterfelt aluminium reflective coating will be required or suitable mineral chippings**

**** Underlay to be nailed when used onto timber tongued and grooved board**

Chesterfelt recommend that all products must be laid in accordance with BS8217 Code of Practise for Built up Felt Roofing
Please refer to Terms and Conditions of Guarantee

www.chesterfelt.co.uk

Tel: 01246 268000

The above is accurate at time of issue and can be subject to change without prior notice. Any deviations from the above must have the approval of Chesterfelt Ltd