

High Performance Torch-on Underlay



Deboflex Underlay is a torch-applied underlay membrane which is designed for use on various types of flat roofing projects including new build and refurbishments, cold roofs and warm roofs using vapour control layers with insulation. It features a glass fibre core which is saturated and coated in bitumen and the upper surface is finished in a burn off film.

When incorporated in a suitably designed and installed multi-layer system, maintained in accordance with BS 8217:2005 - Reinforced bitumen membranes for roofing, Deboflex Underlay will provide reliable performance.

Product Details

Product Code	Roll Length	Roll Width	Pallet Quantity
2203	16m	1m	25 rolls

Key Features & Benefits:

- High performance underlay
- Double-sided burn off film
- Glass fibre core
- Rapid torch-on application

Suitability

To complete a full system, Deboflex Underlay is fitted above the venting base sheet, or a suitable preparation layer, prior to the final waterproofing layer. When used as part of a multi-layer built up roofing system, it provides long-lasting waterproofing performance and is readily suited to

various types of flat roofing projects, including new build and refurbishments, cold roofs and warm roofs using vapour control layers with insulation.

Installation Guidelines

This product should be installed in accordance with manufacturer recommendations and all relevant national standards and codes of practice, including BS 8217:2005 – the code of practice for reinforced bitumen membranes for roofing.

Maintenance and Repair

Routine inspection, cleaning and maintenance of the roof membranes should be based on the recommendation in BS 8217:2005. Should it be damaged either during construction or at later date, then the repairs should be made using the same materials so that the performance of the built-up membranes is retained.

Performance and Key Properties

Characteristic	Test Method	Result	Tolerance
Roll Length	BS EN 1848-1	16m	+/- 150mm
Roll Width	BS EN 1848-1	1m	+/- 1.5%
Roll Weight	BS EN 1849-1	32kg	+/- 5%
Straightness	BS EN 1848-1	PASS	
Visible Defect	BS EN 1850-1	PASS	
Watertightness	EN 1928:2000 Method A	PASS	

Standards

Manufactured in accordance with BS EN 13707:2004+A2:2009 - Flexible sheets for waterproofing. Reinforced bitumen sheets for roof waterproofing.

Handling and Storage

The material should be stored vertically on a firm flat surface and transported stood on end to avoid damage.

Certification

UKCA certified & CE Marked to EN 13707:2004+A2:2009.
CE Certificate Number: 0086-CPR-595938.
UKCA Certificate Number: 0086 CPR 753192.

Health and Safety

Health and Safety should be observed at all times in accordance with HSE and industry guidance. Specific Risk Assessments and Method Statements should be produced by contractors where necessary to ensure Working at Heights, Fire Safety and Manual Handling rules are compliant with current law and regulations. Health and safety data sheets are available for all materials on request from Chesterfelt.

Quality Assurance

Deboflex Underlay is manufactured in accordance with BS EN ISO 9001:2015 - Quality Management Systems (QMS).

Associated Products

Chesterfelt high performance torch-on cap sheets.



Cert No.
0086-CPR-595938



Chesterfelt Ltd Foxwood Way, Sheepbridge, Chesterfield, Derbyshire, S41 9RA
Telephone: 01246 268000 Email: technical@chesterfelt.co.uk Web: chesterfelt.co.uk



All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.